

Power Cleaner F8 500ml

Product Code: 62486

- Citric acid-based cleaner for use in heavily contaminated systems in accordance with BS 7593:2019
- Removes sludge, limescale and other installation and corrosion debris
- Compatible with all metals and materials commonly used in heating systems, including aluminium
- Easy to use, system can operate normally during the cleaning process
- Accelerates all cleaning processes; powerflush, manual and magnetic flush
- Fast-acting, pH Neutral, non-foaming formulation, saves time on-site



Super strength cleaner for heavily contaminated, dirty central heating systems

Physical Properties/Specification

Colour:	Orange
Odour:	Aromatic
Form:	Liquid
pH(conc):	7.2
pH(0.5% soln)	6.5 - 7.7
SG:	1.16 @ 20°C

Application

One 500ml bottle of Power Cleaner F8 is sufficient to clean a large domestic central heating system (130 litres) which covers 97% of UK domestic housing stock. Additional/repeat applications of Power Cleaner F8 may be necessary for systems which have more than 130 litres or 16 radiators, or if systems are very heavily sludged. First, drain and refill the entire system with mains water. For optimum results, the entire system, including dropfeed radiators where fitted, should be completely drained. Preferably, fullbore gate valves with hose connectors should be provided temporarily for this purpose. Motorised and thermostatically controlled valves must be set so that no part of the system is closed off during cleaning or rinsing. Discharges must be made to the foul drain and not to surface water drain.

For open vented systems add Power Cleaner F8 via the headertank. For sealed systems add via a towel rail, a TF1 system filter or another suitable dosing point. Power Cleaner F8 can also be used in conjunction with a powerflushing machine. In this case, please refer to the unit manufacturer's instructions.

Power Cleaner F8 should be circulated for a minimum of one hour at normal operating temperature. However, to remove hardened iron oxides and limescale, the cleaning time can be extended for up to one week under the normal heating cycle. If a radiator still has a cold spot after one hour, increase the flow through the radiator by closing the valves on the other radiators. An additional or repeat dose of Power Cleaner F8 may be necessary in some cases.

Drain and flush thoroughly, at least twice, until the water runs clear. When using Power Cleaner F8 with a powerflushing machine, use dynamic flushing with mains water until the water is clear. Refill the system adding Fernox Protector F1 (or Fernox Protector+ Filter Fluid for systems with an in-line system filter) for long term protection against corrosion and limescale.

In single feed indirect cylinders, e.g."Primatic"or similar, potable water chemicals must be used.

Packaging, Handling and Storage

Power Cleaner F8 is supplied in 500ml bottles. Keep out of reach of children. Do not mix with other chemicals. For further safety information, consult the Safety Data Sheet (SDS).

Single Item				
Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	EAN Barcode
182	88	52	0.600	5014551624863

Outer Carton					
Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	ITF Barcode	Pallet Type
195	265	180	6.130	05014551002104	CP1 1200 x 1000

Updated - 16-Sep-2020 09:47:03